AMENDMENTS TO THE CLAIMS:

Claim 1 (canceled)

2. (Currently Amended) <u>A motor driving device comprising:</u>

a motor; and

a motor driver circuit for controlling motion of the motor,

wherein the motor driver circuit has a function of limiting a current supplied to the motor below a predetermined limit value, and wherein the A-motor driving device—as claimed in claim-1, further-comprising: comprises an adjusting means for adjusting the limit value.

3. (Currently Amended) A motor driving device as claimed in claim [[1]] 2,

wherein the limit value is brought down to a predetermined value that is required to drive the motor so that the motor is driven with a constant current.

4. (Currently Amended) A motor driving device as claimed in claim [[1]] 2,

wherein the limit value is brought up above a predetermined value that is required to drive the motor so that the motor is driven in a saturated state.

5. (Currently Amended) A motor driving device as claimed in claim [[1]]

wherein the motor driving device has a USB (universal serial bus) as an interface bus and is designed as a bus-powered device that is supplied with electric power via the USB.

6. (Currently Amended) A motor driving device as claimed in claim [[1]] 2,

wherein the motor driving device is a disk device and the motor is a stepping motor.

7. (Original) A motor driving device comprising:

a motor;

a motor driver circuit for controlling motion of the motor; and

a resistor provided in a line by way of which electric power is supplied to the motor,

wherein the motor driver circuit limits a current supplied to the motor below a predetermined limit value by performing feedback control in such a way that a voltage across the resistor is kept below a predetermined voltage.

8. (Original) A motor driving device as claimed in claim 7, wherein the limit value can be adjusted by varying the resistance of the resistor.

B

<u>2</u>,

9. (Original) A motor driving device as claimed in claim 7,

wherein the limit value is brought down to a predetermined value that is required to drive the motor so that the motor is driven with a constant current.

10. (Original) A motor driving device as claimed in claim 7,

wherein the limit value is brought up above a predetermined value that is required to drive the motor so that the motor is driven in a saturated state.

11. (Original) A motor driving device as claimed in claim 7,

wherein the motor driving device has a USB (universal serial bus) as an interface bus and is designed as a bus-powered device that is supplied with electric power via the USB.

12. (Original) A motor driving device as claimed in claim 7, wherein the motor driving device is a disk device and the motor is a stepping

13. (Original) A disk device comprising:

a head for writing and reading data to and from a disk;

a stepping motor for moving the head stepwise in a direction of a radius of the disk;

a stepping motor driver circuit for controlling the stepping motor; and

motor.

a resistor provided in a line by way of which electric power is supplied to the stepping motor,

wherein the stepping motor driver circuit limits a current supplied to the stepping motor below a predetermined limit value by performing feedback control in such a way that a voltage across the resistor is kept below a predetermined voltage.

- 14. (Original) A disk device as claimed in claim 13, wherein the limit value can be adjusted by varying the resistance of the resistor.
- 15. (Original) A disk device as claimed in claim 13,

 wherein the limit value is brought down to a predetermined value that is required to drive to stepping motor so that the stepping motor is driven with a constant current.
 - wherein the limit value is brought up above a predetermined value that is required to drive the stepping motor so that the stepping motor is driving in a saturated state.

A disk device as claimed in claim 13,

17. (Original) A disk device as claimed in claim 13, wherein the disk device has a USB (universal serial bus) as a interface bus and is designed as a bus-powered device that is supplied with electric power via the USB.

16.

(Original)